

SSR - 005 Pinecone



SSR-008 Reed



SSR - 002 Cognac



SSR-001 Bourbon



SSR - 005 Pinecone




SSR - 004 Madeira




SSR - 006 Pomegranate



SSR - 009 Truffle



SSR - 007 Prussian Blue



SSR-003 Eclipse

SAN REMO

HIGH PERFORMANCE VINYL

	Content	Weight Per Lin Yd	Finish / Treatments	Directional / Railroaded	Abrasion	Flammability*	Cleaning Code
FABRIC SPECIFICATIONS	Face: 100% Vinyl Backing: 75% Polyester, 25% Cotton	36.0 oz	Standard Acrylic Topcoat	Yes / No	100,000 Double Rubs	California Bulletin 117-E FMVSS 302 NFPA 260 Class 1 UFAC Class 1	W

Roll Width - 54"

San Remo meets or exceeds ACT® Performance Guidelines.



Please visit our website **www.burchfabrics.com** for full specification information as well as cleaning guidelines.

Dye lots may vary from samples shown.

Final determination of the suitability of this product for an application rests with the user.

*Flammability: This term and any corresponding data refer to the typical performance in the specific tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.





* To Experience the Distressed Leather Appeal of Vintage



HIGH PERFORMANCE VINYL

	Content	Weight Per Lin Yd	Finish / Treatments	Directional / Railroaded	Abrasion	Flammability*	Cleaning Code
FABRIC SPECIFICATIONS	Face: 100% Vinyl Backing: 75% Polyester, 25% Cotton	36.0 oz	Standard Acrylic Topcoat	No / No	50,000 Double Rubs	California Bulletin 117-E FMVSS 302 NFPA 260 Class 1 UFAC Class 1	W

Roll Width - 54"

Vintage meets or exceeds ACT® Performance Guidelines.



Please visit our website www.burchfabrics.com for full specification information as well as cleaning guidelines.

Dye lots may vary from samples shown.

Final determination of the suitability of this product for an application rests with the user.

* Experience the Distressed Leather Appeal of Vintage.

Vintage is specifically formulated to emulate the appearance of fine waxed pull-up leather. It is designed to distress and lighten when it is sewn, tufted, stretched or creased.



^{*}Flammability: This term and any corresponding data refer to the typical performance in the specific tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.